International
Building
CODE
20000
> 2006

# 2006 INTERNATIONAL

Plan Review #	 • •
Date:	
Valuation:	
Fee:	

CODE -		rian neview #		
	<b>BUILDING CODE®</b>	Date:		
		Valuation: Fee:		
>24	906 PLAN REVIEW RECORD	Fee:		
JURISI	DICTION:	가는 사이 사이 문제 사람이 되는 것 같은 사람들은 것 같은 사람들이 되었다. 같은 보이 아이들의 사람들은 이름을 가고 못 가는 것을 하고 있었다.		
	DICTION:(City, County, Township, et	<b>c)</b>		
BUILD	ING LOCATION: (Street address)			
	회사 있는 나는 사람들에 작용되었는데 회사 이름을 하시고 있습니다. 하는 아니는 이 사기를 하는 점점 하를 하고 있었다면 하는 것은 다른	아이지 아ું 못했다. 그 얼마나 내 그는 아니라 마음이 하는데 되었다. 그는데 아이를 하는데 그 사람이 되었다.		
BUILD	ING DESCRIPTION:			
<u> </u>				
REVIE\	WED BY:			
Numerals	indicated in parenthesis are applicable code sections of the 2006 International Bu			
provisions	mited to those code sections specifically identified herein. This record references or which may be applicable to specific buildings. This record is designed to be used to	ommonly applicable code sections. It does not reference all code only by those who are knowledgeable and capable of exercising		
competent	i judgement in evaluating construction documents for code compliance.			
	CORRECTION LIST			
		Code		
No.	DESCRIPTION	Section		



Copyright, 2006, International Code Council, Inc. Reproduction by any means is prohibited. ICC is the trademark of International Code Council, Inc., and is registered in the U.S. Patent and Trademark Office. For additional forms, contact:

INTERNATIONAL CODE COUNCIL, INC.
PHONE 1-888-ICC-SAFE (422-7233) • WWW.ICCSAFE.ORG

	CORRECTION LIST (cont'd.)	
No.	DESCRIPTION	Code Section
		·
•		
		100
		,
		.,
<u>.</u>		
15		

CORRECTION LIST (cont'd.)				
No.	DESCRIPTION	Code Section		
•				
		,		
-				
		:		

CÖRRECTION LIST (cont'd.)				
No.	DESCRIPTION	Code Section		
TIO.	·	Coolion		
		ļ		
		<del> </del>		
		ļ		
:				
		ļ		
`				
	·			
		,		
		:		
		-		
,				
	L			

NOTES: N.R. — Not required N.A. — Not applicable

## **ADMINISTRATION (Chapter 1)**

Complete construction documents (106.1, 106.2)	Signed/sealed construction documents (106.1, State laws vary)
BUILDING PLANNING	G (Chapters 3, 4, 5, 6)
OCCUPANCY CLASSIFIC	CATION (302 - 312, 508)
Single Occupancy (302.1)	Incidental uses (508.2)
Mixed Occupancy (508.3)	Accessory occupancies (508.3.1)
GENERAL BUILDING LIMI	TATIONS (Chapters 5 & 6)
Apply Case 1 to determine the allowable height and area an single occupancy or nonseparated mixed occupancies. App permitted types of construction for a building containing sep	ly Case 2 to determine the allowable height and area and
Allowable tabular area, <i>A<sub>t</sub></i> ( <i>Table 503</i> )	Frontage
Area Increase Factor due to Frontage, <i>I<sub>f</sub></i> (506.2)	(506.2) North East South West
Area Increase Factor due to automatic sprinklers, <i>I</i> <sub>s</sub> (506.3) +	Total Frontage (F)ft. Perimeter (P)ft.  Width of open space (W) =
Conversion factor =	Area Increase Factor due to Frontage, $I_{f=}$ (506.2) $I_{f} = \left[\frac{F}{P} - 0.25\right] \frac{W}{30}$
Using Table 503, identify the allowable height and area of the mixed occupancies. Construction types that provide an allowater area and allowable heights (as modified by Section 504) equa	
DETERMINE CONSTRUCTION TYPE	CHECK ALLOWABLE AREA (506.4)
Actual building area ft <sup>2</sup>	Allowable area per floor (A <sub>a</sub> )
Adjusted building areaft <sup>2</sup> actual building area ÷ conversion factor	$\begin{array}{cccccccccccccccccccccccccccccccccccc$
Actual building heightfeetstories	Total floor area (all stories)ft <sup>2</sup>
Allowable building heightfeetstories	Allowable floor area (all stories)
Permitted types of construction	× =ft²
Type of construction assumed for review (602.1.1)	Allowable area per floor number of stories (A <sub>s</sub> ) (maximum 3)  Compliance verified (Single Occ. or Nonsen.)

#### CASE 2 — SEPARATED MIXED OCCUPANCIES (508.3.3)

Using Table 503, identify the allowable height and area of each of the separated occupancies within the building. Construction types that provide, for each story of the building, tabular areas (as modified by Section 506) which result in a sum of the ratios of 1.00 or less and allowable heights (as modified by Section 504) equal to or greater than the actual height of the occupancy are permitted.

	_	Actual	Adjusted	Actua	* * *	Allowable	
Story	Group	floor area	floor area*	heigh	t	height	
	•	ft <sup>2</sup>	ft <sup>2</sup>	ft	stories	ft	stories
		ft <sup>2</sup>	ft <sup>2</sup>	ft	stories	ft	stories
		ft²	ft <sup>2</sup>	_ <u> </u>	stories	ft	stories
		ft <sup>2</sup>	ft <sup>2</sup>	ft	stories	ft	stories
		ft <sup>2</sup>	ft <sup>2</sup>	<u> </u>	stories	ft	stories
		ft <sup>2</sup>	ft <sup>2</sup>	ft	stories	ft	stories
		ft <sup>2</sup>	ft <sup>2</sup>	ft	stories	<u>.                                    </u>	stories
Area ratio	(single floor)=	= >	floor area *	=+	<del>+</del>	-+=	≤100
***************************************			a, $A_t$ (Table 503)				
		oor area + conversion	factor	$(x_1,x_1,y_2,\dots,x_n) = x_1 \frac{1}{2} $	en end both		
CHECK A	LLOWABLE A	AREA (506.4)					
Total area	atio (all floors	;) =		Permitted types	of construction	n	
	. ,			T Official types			
Two-story b	ouildings (Tota	al area ratio ≤ 2)		Type of constru			
				for review (60	2.1.1)		
Three or m	ore story build	dings		Compliance ver	ified (Mixed Od	oc Senarated)	
(Total area		<b>3</b> -		Compliance ver	ilica (iviixea Ot	sc. Geparated)	·
			MEZZAN	INES (505)			
	_ Area lir	mitation <i>(505.2)</i>		· · · · · · · · · · · · · · · · · · ·	Openness (5	505.4)	
	_ Egress	(505.3)			Equipment p	latforms (505.5)	
	•			*****			
			NI IMITED ADE	A BUILDINGS (50	, : \ <del>7</del> \		
				A BUILDINGS (SC			
	_ Nonsp	inklered, one stor	y <i>(507.2</i> )		Group H occ	upancies <i>(507.7)</i>	
7741	Sprinkl	ered, one story <i>(5</i>	07.3)	TANK A	Aircraft paint	hangar <i>(507.8)</i>	
	_ Two sto	ory (507.4)			Group E buil	dings <i>(507.9)</i>	
	Reduce	ed open space <i>(50</i>	)7 <u>5</u> )		-	e theaters <i>(507.1</i>	<b>(1)</b>
	_ Group	A-3 buildings <i>(507</i>	.6)		(507.11)	ll buildings/anchor	stores
4.3			SPECIAL PRO	OVISIONS (509)	(001777)	for the second of the	• • • •
	Special Control	l condition annies		(000)			
	_ Special	condition applica	ble (509.1)		Compliance	verified	
SPEC	IAL DETAI	LED REQUIRE	EMENTS BAS	SED ON USE A	ND OCCUE	PANCY (Chan	ter 4)
	MALL BUILD						.01,
OOVERLED		` ,	is a second of the second of t		Smoke con		
****	_ Egress	(402.4, 402.12)	, e		Kiosk requi	rements (402.10)	
	_ Mall wi	dth (402.5)			Playground	structures (402.1	1)
	Unlimit	ed area <i>(402.6)</i>		g e	Emergency	voice/alarm	
	Fire se	parations (402.7)			(402.13,		en e
		atic sprinkler syste	m (402.9)		Plastic sign	s (402.15)	
			•		` •	nent access (402.	16)
	Standpi	ipe system (402.8	.1)		i ne departi	110111 a00655 (402.	10)

HIGH-RISE BUILDINGS (403)	OTHER SPECIAL USE AND OCCUPANCY					
Automatic sprinkler system (403.2)	Underground structures (405)  Motor-vehicle-related occupancies (406, 509)					
Fire-resistance rating reduction (403.3)  Automatic fire detection (403.5)						
Emergency voice/alarm systems	Group I-2 (407)					
(403.6)	Group I-3 (408)  Motion picture projection rooms (409)					
Fire department communication (403.7)						
Fire command center (403.8)	Stages and platforms (410) Special amusement buildings (411)					
Elevators (403.9)						
Standby power (403.10)	Aircraft-related occupancies (412)					
Emergency power (403.11)	Combustible storage (413)					
Stairway doors (403.12)	Hazardous materials (307.1, 414)					
Smokeproof exit (403.13)	Groups H-1, H-2, H-3, H-4, and H-5 <i>(415)</i>					
ATRIUMS (404)	Application of flammable finishes (416)					
Atrium use (404.2)	Drying rooms (417)					
Automatic sprinkler system (404.3)	Organic coatings manufacturing (418)					
Smoke control (404.4) Enclosure (404.5)	Group I-1, R-1, R-2, R-3 (419)					
Standby power (404.6)	Hydrogen cutoff rooms (420)					
Interior finish (404.7)						
Travel distance (404.8)						
	(Chapters 6, 7, 8, 9)					
FIRE-RESISTANCE-RATED CONSTRUC	CTION (Tables 601 & 602 and Chapter 7)					
<b>Note:</b> Entry in indicates required rating in hours. NC indicates noncombustible construction required.	BUILDING ELEMENTS (Table 601)					
Construction classification (602)	Structural frame (714)					
COMBUSTIBILITY (602.2, 602.3, 602.4, 602.5, 603)	Interior bearing walls					
Exterior walls	Interior nonbearing walls					
Interior elements	Floor construction (711)					
Roof						
FIRE-RESISTANCE RATINGS AND FIRE TESTS (703)	Roof construction (711)					
Ratings / Combustibility (703.2, 703.4)	EXTERIOR WALLS (507, Table 602, 704, 706.6)  North East South West					
Alternative methods (703.3, 718, 720, 721)	Fire separation distance					
	Bearing					
	Nonhearing					

E>	CTERIOR WAL	LS (continued)	SHAFTS (707)			
		Opening protection (704.8, 704.12, 704.14)	,	Exceptions (707.2)		
		Vertical fire spread protection		Construction (707.3 - 707.14)		
		(704.9, 704.10)	OTHER FIRE-R	ESISTANT CONSTRUCTION		
, [	]	Parapets (704.11)		Fire walls (705)		
FI	RE BARRIERS	5 (706)	1. A. A.			
		Shaft enclosures (706.3.1)		Fire partitions (708)		
	]	Exit enclosures/exit passageway (706.3.2, 706.3.3)		Smoke barriers (709)		
		(100.3.2, 100.3.3)		Smoke partitions (710)		
	, .	Horizontal exits (706.3.4)		Penetrations (712)		
		Atriums (706.3.5)	<u> </u>	Fire-resistant joint systems (713)		
	<u></u>	Autums (700.3.3)		Opening protectives (715)		
		Incidental use areas (706.3.6)	****	Dampers (716)		
		Control areas (706.3.7)		Concealed spaces (717)		
	]	Mixed occupancy and fire area separations (706.3.8, 706.3.9)	CUES (Chanta	Thermal- and sound-insulating materials (719)		
		INTERIOR FINIS	oneo (Cnaptei			
		Smoke development (803.1)	· · · · · · · · · · · · · · · · · · ·	Floor finish (804)		
		Flame spread (803.1)		Decorations and trim (806)		
		Non-textile finish (803.2)				
		FIRE PROTECT	ΓΙΟΝ (Chapter	9)		
	JTOMATIC SP 'here required)	RINKLER SYSTEMS (903)		Additional required systems (Table 903.2.13)		
		Assembly (A-1, A-2, A-3, A-4, A-5) (903.2.1)	ALITOMATIC SE	International Fire Code (IFC 903.2.13) PRINKLER SYSTEMS* (903)		
		Educational (E) (903.2.2)	(Design)	(000)		
		Factory/Industrial (F-1) (903.2.3)	<u> </u>	Shop drawings (106.1.1.1)		
		High-hazard (H-1, H-2, H-3, H-4, H-5) (903.2.4)		NFPA 13 system (903.3.1.1)		
		(903.2.4) Institutional (I-1, I-2, I-3, I-4)		NFPA 13R system (903.3.1.2)		
		(407.5, 903.2.5)	<u></u> .	NFPA 13D system (903.3.1.3)  Quick-response and residential heads		
		Mercantile (M) (903.2.6)		(903.3.2)		
		Residential (R) (903.2.7)		Actuation (903.3.4)		
_		Storage/Repair garage (S-1) (903.2.8)		Water supplies (903.3.5)		
-	<del> </del>	Parking garages (903.2.9) Windowless story (903.2.10.1)		Hose threads (903.3.6)		
		Rubbish and linen chutes (903.2.10.2)		Sprinkler monitoring and alarms (903.4, 907.13)		
	<u> </u>	Buildings over 55 ft. high (903.2.10.3)	* Also see Fire C	Code Sprinkler Plan Review Record		
	•	Incidental uses (508.2)	AISO SEC FILE C	POGO OPITIMISTI FIGHT MEVIEW MECULU		

ALTERNATIVE AUTOMATIC FIRE-EXTINGUISHING SYSTEMS (904)	Single/multiple station smoke alarms (907.2.10)		
Installation (904.3)	High-rise buildings (907.2.12)		
Wet-chemical systems (904.5)	Atriums (907.2.13)		
Dry-chemical systems (904.6)	Other buildings/areas (907.2.11, 907.2.14 - 907.2.23)		
Foam systems (904.7)	FIRE ALARM AND DETECTION SYSTEMS (907)		
Carbon dioxide systems (904.8)	(Design)		
Halon systems (904.9)	Residential smoke alarm power source		
Clean-agent systems (904.10)	(907.2.10.2)		
Commercial cooking systems (904.2.1, 904.11)	Residential smoke alarm interconnection (907.2.10.3)		
STANDPIPE SYSTEMS (905)	Location/Power supply/Wiring (907.3 - 907.5)		
Installation standards (905.2)			
Building height (905.3.1)	Activation/Presignal/Zones (907.6 - 907.8)		
Group A (905.3.2)	Alarm notification appliances (907.9)		
Covered mails (905.3.3)	Detectors (907.10 - 907.12)		
Stages (905.3.4)	Monitoring (907.14)		
Underground buildings (905.3.5)	EMERGENCY ALARM SYSTEMS (908)		
Helistops/heliports (905.3.6)	Detection system applicable		
Marinas/boatyards (905.3.7)	(908.1 - 908.6)		
Hose connections and locations	SMOKE CONTROL SYSTEMS (909)		
(905.1, 905.4, 905.5, 905.6)	Where required (402.9, 404.4, 405.5, 408.8, 410.3.7.2, 1020.1.7,		
Cabinets (905.7)	1025.6.2.1)		
Dry standpipes (905.8)	Design requirements (909.1 - 909.4)		
Valve supervision (905.9)	Smoke barriers (909.5)		
PORTABLE FIRE EXTINGUISHERS (906)	Pressurization method (909.6)		
Required locations - IFC (906.1)	Airflow design method (909.7)		
FIRE ALARM AND DETECTION SYSTEMS (907) (Where required)	Exhaust method (909.8)		
	Design fire (909.9)		
Construction documents (907.1.1)	Equipment/Power (909.10, 909.11)		
Assembly (A-1, A-2, A-3, A-4, A-5) (907.2.1)	Detection and control (909.12 - 909.18)		
Business (B) (907.2.2)	Smokeproof enclosures (909.20)		
Educational (E) (907.2.3)	SMOKE AND HEAT VENTS (910)		
Factory (F-1, F-2) (907.2.4)	Requirements (910.1 - 910.3)		
High-hazard (H-1, H-2, H-3, H-4, H-5) (907.2.5)	Mechanical alternative (910.4)		
,	FIRE COMMAND CENTER (911)		
Institutional (I-1, I-2, I-3, I-4) (907.2.6)	Features (911.1)		
Mercantile (M) (907.2.7)	FIRE DEPARTMENT CONNECTIONS (912)		
Residential (R-1, R-2) (907.2.8, 907.2.9)	Installation (912.1 - 912.5)		

# OCCUPANT NEEDS (Chapters 10, 11, 12)

#### MEANS OF EGRESS (Chapter 10)

OCCUPANT LOAD (1004.1.1 and Table 1004.1.1)					CAPACITY OF EGRESS COMPONENTS (1005.1 and Table 1005.1)			
Location	Floor	Sq.ft./	Occt.	Other occt.	Total	Egress width (inc	ch/occupant)	
	Area <sup>-</sup>	person	load	loads		Stairways		
<del></del>	· · · · · · · · · · · · · · · · · · ·	,				Other egress	components	<u>.                                    </u>
				<del>, , , , , , , , , , , , , , , , , , , </del>		CAPACITY		
						Location	Stairways	Other egress components
		· · · · · · -						
					<u></u>			
			<del>.</del>					
								:
			<u> </u>					
					·			
	-							
					· ———			
							(ITS (1019.1, 1019.	
	·					Location	Required	Shown
15								
		•		·		<del></del>	(.	
			· · · · · · · · · · · · · · · · · · ·					·
							<del></del>	

#### **MEANS OF EGRESS (continued)**

#### **GENERAL MEANS OF EGRESS**

Design requirements (1003.2 - 1003.7)	Door landings/Thresholds/Arrangement (1008.1.4 -1008.1.7)
Means of egress illumination (1006)	Door hardware (1008.1.8, 1008.1.9)
Exit signs (1011)	Stairways <i>(1009)</i>
Accessible means of egress (1007)	Roof access (1009.11)
Means of egress doors (1008.1-1008.1.2)	
Special doors/Gates/Turnstiles	Ramps (1010)
(1008.1.3, 1008.2, 1008.3)	Handrails (1012)
	Guards (1013)
en e	ACCESS
Door number and arrangement (1014.2	Aisles (1014.4)
Common path of egress travel (1014.3)	Egress balconies (1014.5, 1016.3)
Exit access travel distance (1016.1)	Corridors (1017)
(1010.4)	Air movement in corridors (1017.4)
EXITS / EX	IT DISCHARGE
Exits/Exit doors (1018, 1019)	Horizontal exits (1022)
Vertical exit enclosures (1020)	Exterior exit ramps/stairways (1023)
Exit passageways (1021)	Exit discharge (1024)
OTHER MEA	ANS OF EGRESS
Miscellaneous egress requirements (1015.3 - 1015.6)	Assembly aisles & features (1025.6 - 1025.15)
Bleachers (1025.1.1)	Emergency escape and rescue (1026)
Assembly exits & egress (1025.2 - 1025.5)	and the control of th
ACCESSIBIL	ITY* (Chapter 11)
Scoping requirements (1103)	Dwelling units and sleeping units (1107)
Accessible route (1104)	Special occupancies (1108)
Accessible entrances (1105)	Features and facilities (1109)
Parking and passenger loading (1106)	Signage (1110)

\*Also see Accessibility Plan Review Record

<sup>-11-</sup>

#### **INTERIOR ENVIRONMENT (Chapter 12)**

	_	the state of the s	
	Ventilation openings (1203)*	<del> </del>	Sound transmission (1207)
	Temperature control (1204)	·	Interior space dimensions (1208)
<del> </del>	Lighting (1205)		Access to unoccupied spaces (1209)
	Yards or courts (1206)	·	Surrounding materials (1210, 2509)
	*Also see Mechanical	Code Plan Review I	Record
	BUILDING ENVELOP  *See Energy Conservation	•	
	EXTERIOR WA	LLS (Chapter	14)
	Performance requirements (1403)	,	Exterior wall coverings/MCM's (1405,
	Materials (1404)		1407)
		· <u>· · · · · · · · · · · · · · · · · · </u>	Combustible material restrictions (1406)
	ROOF ASSEMBLIES AND ROO	FTOP STRUCT	JRES (Chapter 15)
	Weather protection (1503)		Materials (1506)
Flashing (1503.2, 1507.2.9, 1507.3.9,		Roof coverings (1507)	
1507.5.6, 1507.7.6, 1507.8.7, 1507.9.8)			Roof insulation (1508)
	Performance requirements (1504)		Rooftop structures (1509)
	Fire classification (1505)		Reroofing (1510)
-	STRUCTURAL SYSTE	MS (Chapt	ers 16, 17, 18)
	STRUCTURAL I	DESIGN (Chapt	er 16)
			,
STRUCTURAL	L DESIGN CALCULATIONS	<del></del>	Live load reduction (1603.1.1, 1607.9, 1607.10)
Submitted for all structural members (106.1, 106.1.1)			Roof live loads (1603.1.2, 1607.11)
DESIGNIOA	DS ON CONSTRUCTION DOCUMENTS	Roof snow loads	s (1603.1.3, 1608; Chapter 7 of ASCE 7)
DESIGN LOADS ON CONSTRUCTION DOCUMENTS (1603)			Ground snow load, <i>pg</i> (1608.2; 7.2 of ASCE 7)
Uniformly distr	ibuted floor live loads (1603.1.1, Table 1607.1)	. ;	If $p_g > 10$ psf, flat-roof snow load, $p_f(7.3 \text{ of } ASCE 7)$
Floor Area	a Use Loads Shown		If $p_g > 10$ psf, snow exposure factor, $C_e$ (Table 7-2, 7.3.1 of ASCE 7)
		<del></del>	If $p_g > 10$ psf, snow load importance factor, <i>I</i> (7.3.3, Table 7-4 of ASCE 7)
			Roof thermal factor, C <sub>t</sub> (Table 7-3, 7.3.2 of ASCE 7)
			Sloped roof snow load, ps (7.4 of ASCE 7)

DESIGN LOADS (continued)	Spectral response coefficients, S <sub>DS</sub> & S <sub>D1</sub> (1613.5.4; 11.4.4 of ASCE 7)
Wind loads (1603.1.4, 1609; Chapter 6 of ASCE 7)	Site class (1613.5.2; 11.4.2 of ASCE 7)
Design procedure (6.1.2 of ASCE 7)	,
Basic wind speed (1609.3; Fig. 6-1 of ASCE 7)	Seismic design category (1613.5.6; 11.6 of ASCE 7)
Occupancy category (Table 1604.5; Table 1-1 of ASCE 7)	Basic seismic-force-resisting system (Table 12.2-1 of ASCE 7)
Wind importance factor, I (Table 6-1, 6.5.5 of ASCE 7)	Response modification coefficient, <i>R</i> , and deflection amplification factor, <i>C<sub>d</sub></i> (Table 12.2-1 of ASCE 7)
Surface roughness/Exposure categories (1609.4; 6.5.6 of ASCE 7)	Analysis procedure (12.0 01 AGCL 1)
Internal pressure coefficient (Fig. 6-5, 6.5.11.1 of ASCE 7)	Design base shear (12.8 of ASCE 7) Flood loads (1603.1.6, 1612)
Component and cladding pressures (6.1.4.2, 6.4.2.2, 6.5.12.4 of ASCE 7,	Flood hazard area (1612.3)
Main wind-force resisting system	Elevation of structure (1612.5)
(6.1.4.1, 6.4.2.1, 6.5.12.2 of ASCE 7,	
Earthquake design data (1603.1.5, 1613; Chapter 11 - 13 and 15 - 23 of ASCE 7)	Concentrated loads (1607.4)
Occupancy category	Partition loads (1607.5)
(Table 1604.5; Table 1-1 of ASCE 7)	Impact loads (1607.8)
Seismic importance factor (11.5.1, Table 11.5-1 of ASCE 7)	1607.7, 1607.12, 1607.13, 1610,
Mapped spectral response acceleration S <sub>s</sub> and S <sub>1</sub> (1613.5.1; 11.4.1 of ASCE 7)	
QUALITY ASSUF	RANCE (Chapter 17)
Approvals/Research report(s)(1703,	(4704.7. 4704.9. 4704.9)
1703.4.2) Report No	(1704.7, 1704.8, 1704.9) Sprayed fire-resistant materials and
Statement of special inspections (1704.1.1, 1705)	coatings (1704.10, 1704.11)
Prefabricated items (1704.2)	EIFS (1704.12)
Steel construction (1704.3)	Smoke control (1704.14)
	Seismic resistance (1707)
Concrete construction (1704.4)	Structural testing/Observations (seismic)
Masonry construction (1704.5)	(1708, 1709)
Wood construction (1704.6)	Testing (other) (1710 - 1715)
Prepared fill and foundations	
SOILS AND FOUNI	DATIONS (Chapter 18)
Soils investigations/Reports (1802.1, 1802.2, 1802.6)	Footings and foundations (1805)
	Retaining walls (1806)
Soil classification (1802.3)	Dampproofing and waterproofing (1807)
Excavation, grading and fill (1803)	
Load-bearing values (1804)	Foundations (other types) (1808 - 1812)

# STRUCTURAL MATERIALS (Chapters 19, 21, 22, 23)

#### CONCRETE (Chapter 19)

Plain and reinforced concrete  design/construction standard	Minimum concrete strength (Table 1904.2.2)
specified (1901.2, 1908)  Construction documents (1901.4)	Cold weather and hot weather construction specified (1905.12, 1905.13)
	Slab provisions (1910)
MASONRY	(Chapter 21)
Design method, construction standard specified (2101.2)	Cold weather and hot weather construction specified (2104.3, 2104.4)
Construction documents (2101.3)	Seismic design (2106)
Construction materials (2103)	Glass unit masonry (2110)
Mortar type (2103.8)	Fireplaces/Heaters/Chimneys (2111, 2112, 2113)
STEEL (C	Chapter 22)
Structural steel design/construction	Steel storage racks (2208)
standard specified (2205)  Open-web steel joist design/construction	Cold-formed steel design/construction standard specified (2209)
standard specified (2206)  Steel cable structures (2207)	Cold-formed steel light-framed design/ construction standard specified (2210)
WOOD (C	Chapter 23)
Design method option used (2301.2)	Fasteners and fastening
MATERIAL STANDARDS / CONSTRUCTION REQUIREMENTS (2303 - 2306)	(2303.6, 2304.9, Table 2304.9.1)  Heavy timber construction (2304.10)
Lumber (2303.1.1)	Shear walls and diaphragms
Wood I-joists (2303.1.2)	(2305, 2306)
Glue-laminated timbers (2303.1.3)	CONVENTIONAL LIGHT-FRAME CONSTRUCTION (2308)
Wood structural panels (2303.1.4, 2304.6, 2304.7)	Limitations satisfied (2308.2)
Fiber-, hard-, & particle-, boards	Wind/Seismic requirements (2308.2.1, 2308.2.2, 2308.11, 2308.12)
(2303.1.5 - 2303.1.7)	Braced walls (2308.3, 2308.9.3)
Decay and termite protection (2303.1.8, 2304.11)	Foundation anchorage (2308.3.3, 2308.6)
Structural composite lumber (2303.1.9)	Floor joists (Tables 2308.8[1], 2308.8[2])
Structural log members (2303.1.10)	Wall studs (Table 2308.9.1)
Round timber poles and piles (2303.1.11)	Girders (Tables 2308.9.5 and 2308.9.6, 2308.7)
Fire-retardant-treated wood (2303.2)	Ceiling joists (Tables 2308.10.2[1],
Hardwood and plywood (2303.3)	2308.10.2[2])
Trusses (2303.4)	Roof rafters (Tables 2308.10.3.[1] - 2308.10.3[6])
Joist hangers and connectors (2303.5)	Roof uplift (2308.10.1)

# NONSTRUCTURAL MATERIALS (Chapters 24, 25, 26)

GLASS AND GLAZING (Chapter 24)

· .	Sloped glazing and skylights (2405)	·	Safety glazing (2406, 2407, 2408, 2409)
<u> </u>	GYPSUM BOARD AND	PLASTER (C	Chapter 25)
	Gypsum board materials (2506, Table 2506.2, Table 2508.1)	· · · · · · · · · · · · · · · · · · ·	Plaster (2507, 2508, 2510 - 2513)
	PLASTIC	(Chapter 26)	
FOAM PLASTIC	INSULATION (2603)		Protection against termites (2603.8)
	Labeling (2603.2, 2603.5.6)	e de la companya de l	Special approval (2603.9)
	Surface-burning characteristics (2603.3, 2603.5.4)	MISCELLANEC	•
	Thermal barrier (2603.4)	<del> </del>	Interior finish and trim (2604)
<u> </u>	Exterior walls/Roofs (2603.5, 2603.6)	· ·	Plastic veneer (2605)
			Light-transmitting plastics (2606 - 2611)
	<b>BUILDING SERVICES*</b>	(Chapters	27, 28, 29, 30)
	ELEVATORS AND CONVE	YING SYSTEM	S (Chapter 30)
	Construction standard specified (3001.2)	)	Hoistway venting (3004)
	Hoistway enclosures (3002)	PARTICULAR AND	Conveying systems (3005)
	Opening protectives (3002.1.1)		Machine rooms (3006)
	Emergency operations (3003)		and the second of the second o
* Also see Electr	rical (Ch.27), Mechanical (Ch.28) and Plui	mbing (Ch.29) Plar	n Review Records
SP	SPECIAL CONSTR  Membrane structures (3102)	UCTION (Cha	en en filosofie de la companya de l La companya de la co
· · · · · · · · · · · · · · · · · · ·	Awnings and canopies/Marquees	LDLSTRIAN	Construction and use (3104.3, 3104.4)
	(3105, 3106)		Separation (3104.5, 3104.10)
	Signs (3107)		Public way <i>(3104.6)</i>
<del> </del>	Radio and television towers (3108)		Egress (3104.7 - 3104.9)
	Swimming pool enclosures (3109)		
*	EXISTING STRUC	TURES (Chap	ter 34)
	Additions, alterations, repairs (3403)	· · · · · · · · · · · · · · · · · · ·	Accessibility (3409)
e e e e e	Fire escapes (3404)		Compliance alternatives (3410)
	Change of occupancy (3406)	\$ . ** S	

### BUILDING EVALUATION SUMMARY (Table 3410.7)

xisting occupancy	No,	Proposed occupancy Number of stories Area per floor Corridor wall rating Required door closers:	Height i	
ype of construction	No,	Area per floor  Corridor wall rating		
ercentage of frontage% completely suppressed: Yes compartmentation: Yes ireresistance rating of vertical opening enclosures ype of HVAC system utomatic fire detection: Yes ire alarm system: Yes	No,	Corridor wall rating		
completely suppressed: Yes compartmentation: Yes ireresistance rating of vertical opening enclosures ype of HVAC system utomatic fire detection: Yes ire alarm system: Yes	No,			
ireresistance rating of vertical opening enclosures  ype of HVAC system utomatic fire detection: Yes ire alarm system: Yes	No,	Required door closers:	res	NO
ireresistance rating of vertical opening enclosures  ype of HVAC system  utomatic fire detection: Yes  ire alarm system: Yes				
ype of HVAC system utomatic fire detection: Yes ire alarm system: Yes				
utomatic fire detection: Yes ire alarm system: Yes		serving number of floors		
ire alarm system: Yes	No .	type and location		
· ——	No,			
		type		
dequate exit routes: Yes	No		Yes	No
laximum exit access travel distance			Yes	
leans of egress emergency lighting: Yes	No	Mixed occupancies:	Yes	No
Safety	Fire	Means		General
arameters	safety (FS)	of egress (ME)		safety (GS)
410.6.1 Building height				
410.6.2 Building area				
410.6.3 Compartmentation				
410.6.4 Tenant and dwelling unit separations				
410.6.5 Corridor walls				
410.6.6 Vertical openings				
				<del>.</del>
410.6.8 Automatic fire detection				
410.6.9 Fire alarm system			· · · · · · · · · · · · · · · · · · ·	
410.6.10 Smoke control	***		1	
410 G 11 Moone of agrees	* * * *			:
410.12 Dead ends	***		* *	
410.13 Max. exit access travel distance	***		a .	
410.6.14 Elevator control				
410.6.15 Means of egress emergency lighting	* * * *		· · · · · · · · · · · · · · · · · · ·	
410.6.16 Mixed occupancies		***		
			<u> </u>	
410.6.17 Automatic sprinklers		÷ 2 =	v.	
410.6.18 Incidental use				
uilding score — total value				
* * * No applicable value to be inserted.	¥		, c	
BUILDING SAFE	TY EVALUA	TION SCORE (Table 3410.9)	•	
ormula Table 3410.7	Table 3410.8	Score	Pass	Fail
S–MFS ≥ 0 (FS) —		(MFS) =		
E-MME ≥ 0 (ME)		(MME) =		
S–MGS ≥ 0 (GS) —		(MGS) =		· · ·
	3.450	- Mandata Claron		
FS = Fire Safety ME = Means of Egress	MFS	= Mandatory Fire Safety		
ME = Means of Egress GS = General Safety	MME MGS	<ul><li>Mandatory Means of Egr</li><li>Mandatory General Safet</li></ul>		
CO - General Salety	IVIGO	- manualory General Sale	У	. •